

Wrocław 25.03.2022



INFORMATION ABOUT SERVICE OF SLIDE AND FOLD GLASS PANELS SYSTEM SLF400

SLF400 Slide and Fold Glass Panel System has a single aluminum main track. The system is capable of carrying frameless glass door panels up to 3000mm height, width up to 750mm and thickness 10mm-12mm.

We recommend to verify the systems performance once a year and, if necessary, adjust the panels on the rollers.

For the efficient operation of the system, it is necessary to clean the inside of the main track with compressed air once a year. **DO NOT USE ANY LIQUIDS OR GREASE.**

Check dust proof bolt keepers once a week. To remove dust and sand use the vacuum cleaner.

The remaining parts of the system do not require the User's intervention.

Covers or every aluminium surface of system should be cleaned according to the instructon of maintenance of the anodizing surface.

Hinges beetwen the panels are made of stainless steel and requires cleaning according to the stainless steel maintanance guide.



Wrocław, 07.04.2022

LOCK MAINTENANCE INSTRUCTIONS

Napoli SLF400 systems are equipped with europrofiles with knobs, which does not require key for opening. The locks and the europrofile doesn't require any special cleaning or lubrication.

The product should not be modified in any way, except in accordance with those modifications described in the instruction.

In order to lock system make sure that all the panels are aligned in straight position and the bolt is placed in the center of the dustproof keeper. In next step make full clockwise turn of the knob. The bolt will be inserted in to the dustproof keeper and the panel will be locked. In order to open the lock please turn the knob counter clockwise. Do not use force during knob rotation in any direction.

Attention:

Please don't push the panels during knob rotation. It may cause difficulties with vertical movement of the bolt and inability of placing/removing it in the dustproof keeper.

